



General	
Marketing Area	Asia, Africa
Transponder	DVB-T2 (Plastic Housing)
Power Voltage	AC 100-240V ~ 50/60 Hz
Power Consumption	< 5W

System	
DDR II	1G bit
FLASH Size	32 M bit

Features	
DVB-T2 Standard	V1.3.1
OSD Language	Multi language
Media playback (MP3, FLAC, JPG, JPEG, MPG, MPEG, VOB, AVI, TS, TRP, M2T, M2TS, MP4, MKV, MOV, DIVX(Optional))	Optional
Record through USBHDD	Yes
Timeshift through USBHDD	Yes
7 days EPG (Electronic Program Guide)	Yes
DVB subtitle	Yes
Teletext	VBI/OSD
Easy first installation	Yes
Channel search with automatic / manual	Yes
TV and radio list handling	Yes
Favorite list editing for both radio and TV	Yes
Parents lock	Yes
Aspect ratio handling	Yes
Timer setting	Yes
LCN	Yes
Copy protection	Full HD 1.3/HDCP 1.2
OTA upgrade	Yes

Dimension	
Body Size	W148 x D110 x H35 mm
Packing Size	W192 x D168 x H55 mm

Decode	
Video Decoder	MPEG-2 MP@HL, AVC/H.264 HP@L4.1, MPEG-4 ASP Supported
Audio Decoder	AAC/AC3/PCM
Video Output Ratio	4:3/16:9/Auto
Video Resolution	1920 * 1080

Tuner & Channel	
RF input connector	IEC Female
Receiving Channel Range	174~230Mhz, 470~862MHz
RF output (Loophrough)	Yes
Modulation	QPSK/ 16QAM/ 64QAM/ 256QAM
Code rate	1/2, 3/5, 2/3, 3/4, 4/5, 5/6, 7/8
Band width	6/7/8 MHz
FFT size	1K, 2K, 4K, 16K, 32K
Guard interval	1/128, 1/32, 1/16, 19/256, 1/8, 19/128, 1/4

Terminal	
L/R Audio Output	Yes
CVBS Video Output	Yes
S-Video Output	No
TV SCART	No
Optical output	No
External IR	Yes
Full HD output	Yes
USB 2.0	Yes
Component output	Optional

Front Panel	
Display Type	Red/Type
Infra-red receiver	Yes
Front panel keyboard	Yes
Power indicator (LED)	Yes

Accessories	
Remote control with battery	Yes
Full HD cable	Optional
AV cable	Optional
IB and Warranty Card	Yes